

AIR OPERATED GREASE PUMP



A65-G

MODEL	A65-G
Capacity	20L
Air Input Pressure	4 ~ 9kg / cm ²
Pressure Ratio	45 : 1
Grease Output Pressure	180 ~ 405kg/cm ²
Deliver Rate	30cc / sec
Hose Length	10 ft
N. W.	20.9 kgs
G. W.	23.4 kgs
Cuft	6.2'

Feature

Air Operated Grease Pump uses air as power to suck grease into lubrication points. It is suitable for using with machines, automobiles, and vessels, etc. It is a very useful tool for lubrication and maintenance.

Lubricant

Suitable for 00#~2# grease. Operating in cold area or higher viscosity grease, suggest using with follower plate.



A75-G

MODEL	A75-G
Capacity	200L
Air Input Pressure	4 ~ 9kg / cm ²
Pressure Ratio	45 : 1
Grease Output Pressure	180 ~ 405kg/cm ²
Deliver Rate	30cc / sec
Hose Length	20 ft
N. W.	26.0 kgs
G. W.	29.7 kgs
Cuft	2.8'

Feature

Air Operated Grease Pump uses air as power to suck grease into lubrication points. It is suitable for using with machines, automobiles, and vessels, etc. It is a very useful tool for lubrication and maintenance.

Lubricant

Suitable for 00#~2# original 200L grease reservoir.

AIR OPERATED OIL PUMP

A30-O



MODEL	A30-O
Capacity	30L
Air Input Pressure	4 ~ 9kg / cm ²
Pressure Ratio	5 : 1
Oil Output Pressure	20 ~ 45kg/cm ²
Deliver Rate	16L / min
Hose Length	10 ft
N. W.	20.0 kgs
G. W.	23.0 kgs
Cuft	6.2'



Feature

Air Operated Oil Pumps' out-looking are different based on reservoir capacity, but feature are the same and pump ratio have 5:1 and 16:1. It is equipped with the special pressure stabilizer that may output the oil more smoothly and steadily. The flow meter is an optional extra.

Lubricant

Pressure ratio 5:1 suitable for 0#~120# oil.
Pressure ratio 16:1 suitable for 140#~200#gear oil.

A95-O



A95-OS

MODEL	A95-O	A95-OS
Capacity	200L	200L
Air Input Pressure	4 ~ 9kg / cm ²	4 ~ 9kg / cm ²
Pressure Ratio	1 : 1	1 : 1
Oil Output Pressure	4 ~ 9 kg/cm ²	12 ~ 27kg/cm ²
Deliver Rate	23 ~ 30L / min	23 ~ 30L / min
Hose Length	20 ft	-
N. W.	6.2 kgs	9.2 kgs
G. W.	7.5 kgs	11.2 kgs
Cuft	0.8'	0.8'

Feature

There are 2 different types of Air Operated Oil Pump, which pressure ratio are of 1:1 and 3:1. The feature is that the oil transmission is in great volume, so it is applicable for greater amount of oil or gear oil transmission in between shorter distance.

Lubricant

Pressure ratio 1:1 suitable for 0#~120# oil.
Pressure ratio 3:1 suitable for 140#~200#gear oil.

HAND OPERATED GREASE PUMP

H20G



MODEL	H20-G
Capacity	20L
Delivery Rate	4cc / cycle
Hose Length	6.0 ft
N. W.	7.0 kgs
G. W.	9.5 kgs
Cuft	2.2'

Hand Operated Grease Pump with reservoir capacity 20L. It is using for automobiles and machines maintenance and lubrication.

HAND OPERATOR OIL PUMP

MODEL	H20-O
Capacity	20L
Delivery Rate	65cc / cycle
Hose Length	6.5 ft
N. W.	7.0 kgs
G. W.	9.5 kgs
Cuft	2.2'

H20-O



ACCESSORIES



P- 002

Flow Meter



P- 003

Oil Gun



P- 002NTE

Digital Flow Meter



P- 004

**Oil Gun with
Flow Meter**

P- 004AE

**Oil Gun with
Digital Meter**



P- 002AE

Digital Flow Meter

P- 005

**High Pressure
Grease Gun**



P- 007

Identify with digital number.
accurate, clear, and restorable.
Also, accumulation of flow is available.