



10, 30, 40, 60, 100, 100T(S), 150T, 200T

MODEL		10 T	30 T	40 T	60 T	100 T	150 T	200 T
OVERALL HEIGHT (A)	M.M.	1180	1730	1810	1930	2070	2270	1580
WORKING WIDTH (B)	M.M.	455	560	800	800	1150	1150	520
FRAME WIDTH (C)	M.M.	550	760	1000	1080	1505	1505	680
OVERALL WIDTH (D)	M.M.	650	1000	1255	1295	1745	2110	770
WORKING WIDTH OF SIDE (E)	M.M.	100	200	230	305	455	460	230
FRAME WIDTH OF SIDE (F)	M.M.	200	280	310	390	510	685	250
OVERALL WIDTH OF SIDE (G)	M.M.	430	685	770	915	1150	1345	430
FRAME HOLE (H)	M.M.	25	32	32	40	52	52	27
DISTANCE BETWEEN FRAME HOLE (I)	M.M.	126	140	133	133	133	133	135
PISTON ROD DIA (J)	M.M.	52	70	75	89	98	116	50
RAM STROKE (K)	M.M.	135	150	150	185	235	235	140
WORKING HEIGHT RAM TO TABLE (L)	M.M.	585	905	830	830	835	1145	930
NET WEIGHT	KGS.	75	250	420	665	1575	2000	150



MODEL	NSP-15
CAPACITY	15 Ton
CYLINDER BORE	80mm
PRESSURE	300kg/cm ²
LENGTH	860mm
WIDTH	850mm
HEIGHT	1640mm
N. W.	196kgs
G. W.	226kgs
CU. FT.	24.1



MODEL	NSP-35
CAPACITY	35 Ton
CYLINDER BORE	125mm
PRESSURE	300kg/cm ²
LENGTH	1080mm
WIDTH	850mm
HEIGHT	1820mm
N. W.	320kgs
G. W.	380kgs
CU. FT.	45.81